



AUSTRALIA'S LARGEST RANGE OF BAL40 BUSHFIRE RATED WINDOWS AND DOORS

AWS has developed and tested an extensive range of Vantage, Elevate™ and ThermalHEART™ Aluminium windows and doors to meet and exceed BCA requirements for compliance under Australian Standard AS3959-2009 for windows and doors in a BAL40 bushfire zone.

These products are engineered, tested and certified to withstand the conditions likely to occur in a BAL40 zone and are designed to help you protect your home whilst still delivering unprecedented style, efficiency and functionality for your lifestyle.

BUSHFIRE RATED SYSTEMS BY **AWS**





AUSTRALIA'S LARGEST RANGE OF BAL40 BUSHFIRE RATED WINDOWS AND DOORS

BUSHFIRE RATED SYSTEMS BY **AWS**

Many Australian homes are located in areas prone to bushfire attack. Changes to the BCA in 2011 and the inclusion of AS3959-2009 have increased the stringency around the selection of windows and doors along with other building materials for new build or renovation projects in bushfire prone areas. These changes are intended to reduce the risk of loss of life or damage to property in bushfire areas.

If you currently live, or plan to build, in a bushfire prone area, there are many precautions you can take to help protect your home and maximise your safety. One of these is the correct selection and installation of bushfire rated window and door systems

AWS now offers Australia's largest range of BAL40 Bushfire rated windows and doors.

For more information about BAL40 rated windows and doors visit our websites:

- www.vantagealuminium.com.au
- www.elevatealuminium.com.au
- www.specifyaws.com.au



All AWS BAL40 rated windows and doors are identified with the BAL40 symbol. This symbol indicates the system has been tested or third party certified for BAL40 compliance.

AWS BAL40 rated systems include:



Vantage Residential Series*



Vantage Designer Series*



Vantage Designer Series | ThermalHEART™*



Elevate™ Commercial Series*



Elevate™ Architectural Series*



Elevate™ Commercial Framing*



Elevate™ Commercial ThermalHEART™*

*Product Exclusions: The following systems are not suitable for use in BAL40 bushfire zones: Series 514, 613, 453 & 463 Double Hung window, Series 614 & 464 ClearVENT™ window, Series 546 Bi-fold window, Series 525 Louvre window, Series 620 CentreGLAZE™ (150mm) framing, Series 407 & 607 FaceLINE™ framing, Series 541, 702 & 704 Sliding doors, Series 411 & 412 Bi-fold doors, Series 417 Sun control shutter, Series 467 Truth™ Awning/Casement window. Products may require specific glass or hardware selections to comply. You must specify BAL40 compliance as a requirement when placing your order.